







11H																			
10H																			
9H																			
8H																			
7H																			
6H																			
5H				V-V															
4H		710	VB348		710	VC462		710	VC462		710	VD570		710	VB366		710	VC480	
3H		748	VA264		748	VA378		748	VA378		748	VA486		748	VA264		748	VA384	
2H		749	VA384		749	VA384		749	VA384		749	VA384		749	VA384		749	VA384	
1H		710	VA312		710	VA312		710	VA312		710	VA312		710	VA312		710	VA312	
N	NOSE	710	VA312	NOSE	710	VA312	NOSE	710	VA312	NOSE	710	VA312	NOSE	710	VA312	NOSE	710	VA312	
1F		710	VA252		710	VA252		710	VA252		710	VA252		710	VA252		710	VA252	
2F		710	VB264		710	VB264		710	VB264		710	VB264		710	VB264		710	VB264	
3F		710	VB342		710	VB342		710	VB342		710	VB342		710	VB342		710	VB342	
4F		710	V-V		710	V-V		710	V-V		710	V-V		710	V-V		710	V-V	
5F																			
6F																			
7F																			
8F																			
9F																			
DRG No.		6.271.4138			6.271.4138			6.271.4138			6.271.4138			6.271.4142			6.271.4142		
TYPE		SPLAY			PWL			PWR			DPW			SPLAY			PWL		
ANGLE		1 IN 9.25 (STR VEE)			1 IN 9.25 (STR VEE)			1 IN 9.25 (STR VEE)			1 IN 9.25 (STR VEE)			1 IN 9.25 (CVD VEE)			1 IN 9.25 (CVD VEE)		

NOTES:

1. WHEN ORDERING CROSSINGS QUOTE THE DRAWING NUMBER SHOWN
2. WELDED LEG LENGTHS CAN BE MANUFACTURED TO SUIT SITE REQUIREMENTS IN ADDITION TO THE LENGTHS SHOWN
3. 1 in 9.25 AND 1 in 10.75 CROSSINGS ARE AVAILABLE WITH LH OR RH WING FRONT CURVED TO RADIUS INDICATED
4. SPREADS ARE GIVEN AT THE END OF THE WELDED ON BS113A LEGS
5. ALL LEGS ARE STRAIGHT EXCEPT WHERE OTHERWISE SHOWN







